

Objectives

- Computability
- Reducibility
- Conclusions

Objectives

- Oh, the places you've been!
- Oh, the places you'll go!

Now, everything comes down to expert knowledge of **algorithms** and **data structures**. If you don't speak fluent **O-notation**, you may have trouble getting your next job at the technology companies in the forefront.

— Larry Freeman

Algorithm Design Patterns

- What are some approaches to solving problems?
- How do they compare in terms of difficulty?

Apr 5, 2019

Sprenkle - CSCI211

3

Algorithm Design Patterns

- Greedy
- Divide-and-conquer
- Dynamic programming
- Duality/network flow

Course Objectives: Given a problem...

You'll recognize when to try an approach

- AND, when to bail out and try something different

Know the steps to solve the problem using the approach

- e.g., breaking it into subproblems, sorting possibilities in some order

Know how to **analyze** the run time of the solution

- e.g., solving recurrence relation

Apr 5, 2019

Sprenkle - CSCI211

4

What Were Our Goals In Finding a Solution?

- **Correctness**
- **Polynomial Time → Efficient**

Apr 5, 2019

Sprenkle - CSCI211

5

POLYNOMIAL-TIME REDUCTIONS

Apr 5, 2019

Sprenkle - CSCI211

6

Classify Problems According to Computational Requirements

Fundamental Question:
Which problems will we be able to solve in practice?

Apr 5, 2019

Sprenkle - CSCI211

7

Classify Problems According to Computational Requirements

Which problems will we be able to solve in practice?

- **Working definition.** [Cobham 1964, Edmonds 1965, Rabin 1966] Those with polynomial-time algorithms.

Yes	Probably no
Shortest path	Longest path
Matching	3D-matching
Min cut	Max cut
2-SAT	3-SAT
Planar 4-color	Planar 3-color
Bipartite vertex cover	Vertex cover
Primality testing	Factoring

Apr 5, 2019

8

Classify Problems According to Computational Requirements

Fundamental Question:

Which problems will we be able to solve in practice?

Working Answer:

Those with polynomial runtimes.


Apr 5, 2019

Sprenkle - CSCI211

9

Classify Problems

Classify problems according to those that can be solved in polynomial-time and those that cannot.



Frustrating news:
Many problems have defied classification.

Chapter 8. Show that problems are “computationally equivalent” and appear to be manifestations of one *really hard* problem.

Examples:

- Given a Turing machine, does it halt in at most k steps?
- Given a board position in an n -by- n generalization of chess, can black guarantee a win?

Apr 5, 2019


Sprenkle - CSCI211

10


The Big Question

NP: “nondeterministic polynomial time”

We can verify that a solution solves the problem in polynomial time



$$P \subseteq NP$$



$$P = NP$$

Are there polynomial-time solutions to NP problems?

Apr 5, 2019

Sprenkle - CSCI211

11




Apr 5, 2019

Sprenkle - CSCI211

12

In the mean time...

Classify problems according to those that can be solved in polynomial-time and those that cannot.



Frustrating news:
Many problems have defied classification.

Chapter 8. Show that problems are "computationally equivalent" and appear to be manifestations of one *really hard* problem.

Examples:

- Given a Turing machine, does it halt in at most k steps?
- Given a board position in an n -by- n generalization of chess, can black guarantee a win?

Apr 5, 2019

Sprenkle - CSCI211

13

NP-Complete Problems

- Problems from many different domains whose complexity is unknown
- NP-completeness and proof that all problems are equivalent is **POWERFUL!**
 - All open complexity questions → **ONE** open question!
- What does this mean?
 - "Computationally hard for practical purposes, but we can't prove it"
 - If you find an NP-Complete problem, you can stop looking for an efficient solution
 - Or figure out efficient solution for ALL NP-complete problems

Apr 5, 2019

Sprenkle - CSCI211

14

Fun Fact: Connecting Chapters 7 and 8

- Richard Karp
 - of the Edmonds-Karp algorithm (max-flow problem on networks)
 - published a paper in complexity theory on "Reducibility Among Combinatorial Problems"
 - proved 21 Problems to be NP-complete



Polynomial-Time Reduction

Suppose we could solve Y in polynomial time.
What else could we solve in polynomial time?

Polynomial-Time Reduction

Suppose we could solve Y in polynomial-time.
What else could we solve in polynomial time?

- **Reduction.** Problem X *polynomially reduces to* problem Y if arbitrary instances of problem X can be solved using:
 - Polynomial number of standard computational steps, *plus*
 - Polynomial number of calls to **oracle** that solves problem Y
 - Assume have a black box that can solve Y

For X + Y

- **Notation:** $X \leq_p Y$
 - “ X is polynomial-time reducible to Y ”
- **Conclusion:** If Y can be solved in polynomial time and $X \leq_p Y$, then X can be solved in polynomial time.

Apr 5, 2019

Sprenkle - CSCI211

17

Polynomial-Time Reduction

- **Purpose.** Classify problems according to *relative difficulty*.
- **Design algorithms.** If $X \leq_p Y$ and Y can be solved in polynomial-time, then X **can** also be solved in polynomial time.
- **Establish intractability.** If $X \leq_p Y$ and X cannot be solved in polynomial-time, then Y **cannot** be solved in polynomial time.
- **Establish equivalence.** If $X \leq_p Y$ and $Y \leq_p X$, we use notation $X \equiv_p Y$.

Apr 5, 2019

Sprenkle - CSCI211

18

Basic Reduction Strategies

- *Reduction by simple equivalence*
- Reduction from special case to general case
- Reduction by encoding with gadgets


Apr 5, 2019

Sprenkle - CSCI211

20

Independent Set

- Given a graph $G = (V, E)$ and an integer k , is there a subset of vertices $S \subseteq V$ such that $|S| \geq k$ and for each edge **at most one** of its endpoints is in S ?



How is this different from the network flow problem?

Ex. Is there an independent set of size ≥ 6 ?

Ex. Is there an independent set of size ≥ 7 ?


Apr 5, 2019

Sprenkle - CSCI211

21

Independent Set

- Given a graph $G = (V, E)$ and an integer k , is there a subset of vertices $S \subseteq V$ such that $|S| \geq k$ and for each edge **at most one** of its endpoints is in S ?



Ex. Is there an independent set of size ≥ 6 ? **Yes**

Ex. Is there an independent set of size ≥ 7 ? **No**

● independent set


Apr 5, 2019

Sprenkle - CSCI211

22

Vertex Cover

- Given a graph $G = (V, E)$ and an integer k , is there a subset of vertices $S \subseteq V$ such that $|S| \leq k$ and for each edge, **at least one** of its endpoints is in S ?



A vertex **covers** an edge.

Application: place guards within an art gallery so that all corridors are visible at any time

Ex. Is there a vertex cover of size ≤ 4 ?

Ex. Is there a vertex cover of size ≤ 3 ?


Apr 5, 2019

Sprenkle - CSCI211

23

Vertex Cover

- Given a graph $G = (V, E)$ and an integer k , is there a subset of vertices $S \subseteq V$ such that $|S| \leq k$ and for each edge, **at least one** of its endpoints is in S ?



Ex. Is there a vertex cover of size ≤ 4 ? **Yes**

Ex. Is there a vertex cover of size ≤ 3 ? **No**

 vertex cover

Apr 5, 2019

Sprenkle - CSCI211

24

Problem

- Not known if finding Independent Set or Vertex Cover can be solved in polynomial time
- BUT**, what can we say about their relative difficulty?


Apr 5, 2019

Sprenkle - CSCI211

25

Vertex Cover and Independent Set

- **Claim.** VERTEX-COVER \equiv_p INDEPENDENT-SET
- **Pf.** We show S is an independent set iff $V - S$ is a vertex cover



Apr 5, 2019

Sprenkle - CSCI211

26

Vertex Cover and Independent Set

- **Claim.** VERTEX-COVER \equiv_p INDEPENDENT-SET
- **Pf.** S is an independent set iff $V - S$ is a vertex cover
- \Rightarrow

Apr 5, 2019

Sprenkle - CSCI211

27

Vertex Cover and Independent Set

- **Claim.** VERTEX-COVER \equiv_p INDEPENDENT-SET
- **Pf.** We show S is an independent set iff $V - S$ is a vertex cover
- \Rightarrow
 - Let S be an independent set
 - Consider an arbitrary edge (u, v)
 - Since S is an independent set $\Rightarrow u \notin S$ or $v \notin S$ or both $\notin S$ $\Rightarrow u \in V - S$ or $v \in V - S$ or both $\in V - S$
 - Thus, $V - S$ covers (u, v)
 - Every edge has at least one end in $V - S$
 - $V - S$ is a vertex cover

Apr 5, 2019

Sprenkle - CSCI211

28

Vertex Cover and Independent Set

- **Claim.** VERTEX-COVER \equiv_p INDEPENDENT-SET
- **Pf.** We show S is an independent set iff $V - S$ is a vertex cover
- \Leftarrow
 - Let $V - S$ be any vertex cover
 - Consider two nodes $u \in S$ and $v \in S$
 - Observe that $(u, v) \notin E$ since $V - S$ is a vertex cover
 - Thus, no two nodes in S are joined by an edge $\Rightarrow S$ independent set

Apr 5, 2019

Sprenkle - CSCI211

29

Using the Previous Result

- Problem X *polynomial reduces to* problem Y if arbitrary instances of problem X can be solved using:
 - Polynomial number of standard computational steps, *plus*
 - Polynomial number of calls to **oracle** that solves problem Y
 - Assume have a black box that can solve Y

How do we show polynomial reduction
for the independent set and vertex cover?

Apr 5, 2019

Sprenkle - CSCI211

30

Summary

- If we have a black box to solve Vertex Cover, can decide whether G has an independent set of size at least k by asking the black box whether G has a vertex cover of size at most $n - k$
- If we have a black box to solve Independent Set, can decide whether G has a vertex cover of size at most k by asking the block box whether G has an independent set of size at least $n - k$

Apr 5, 2019

Sprenkle - CSCI211

31

Basic Reduction Strategies

- *Reduction by simple equivalence*
- Reduction from special case to general case
- Reduction by encoding with gadgets

Apr 5, 2019

Sprenkle - CSCI211

32

Now you “get” this xkcd comic

MY HOBBY:
EMBEDDING NP-COMPLETE PROBLEMS IN RESTAURANT ORDERS

CHOTCHKIES RESTAURANT	
APPETIZERS	
MIXED FRUIT	2.15
FRENCH FRIES	2.75
SIDE SALAD	3.35
HOT WINGS	3.55
MOZZARELLA STICKS	4.20
SAMPLER PLATE	5.80
SANDWICHES	
BARBECUE	6.55

WE'D LIKE EXACTLY \$15.05 WORTH OF APPETIZERS, PLEASE.

... EXACTLY? UHH...

HERE, THESE PAPERS ON THE KNAPSACK PROBLEM MIGHT HELP YOU OUT.

LISTEN, I HAVE SIX OTHER TABLES TO GET TO —

— AS FAST AS POSSIBLE, OF COURSE. WANT SOMETHING ON TRAVELING SALESMAN?

Apr 5, 2019

Sprenkle

How is this a knapsack problem?

From Patrick: Oracle of Bacon

- “Say you wanted to have each of the 1000 best centers of the Hollywood universe in your movie collection at least 20 times. What is the least number of movies you would have to own?”
- Are you trolling me, random Oracle of Bacon user? I'm pretty sure that's an example of the set-cover problem, with n equal to the $\sim 100,000$ movies the top 1000 best centers have appeared in. 2^{10^6} is really big.
 - NP-Complete trolls are the trolliest trolls. At least the problem is decidable.

Apr 5, 2019

Sprenkle - CSCI211

40


P vs NP in *Numbers*

Charlie: Dad, uhm.. I've been working on a problem. P vs. NP. It can't be solved.

Alan: I think you knew that when you started.

Charlie: I could work on it forever. Constantly pushing forward, still never reaching an end.

...



Apr 5, 2019

My Algorithms Approach

- Why problems?
 - Why no implementation until the end?
- Why wiki?
- Research to support decisions

Apr 5, 2019

Sprenkle - CSCI211

42

Final

- Due next Friday, noon (end of exams)
- Can use book, notes, handouts, my lecture notes, Sakai solutions, me (limited)
 - “The status of the P versus NP problem”, article
 - No other outside resources
- Office hours: see BoxNote
 - Starting this afternoon
- Evaluations due Sunday at midnight on Sakai

Apr 5, 2019

Sprenkle - CSCI211

43